

SMART 3000S

Throughput	Up to 280 tests/hour
Modes of Operation	Random, Batch and STAT
Sample Loading	Up to 70 sample tubes Continuous loading, STAT available Barcode reader recognition or analyzer auto numbered Auto read sample info
Reagent Loading	32 reagents on board (20 test items can be simultaneous) Continuous loading Barcode reader recognition
Reaction Cuvette	≤320 (8*40) Continuous loading
Sample Probe Carryover	<1.0 parts per million
Linear Correlation	≥0.999
Accuracy	CV≤3%
Other Features	Liquid level detection, plugged needle alarm, air suction alarm Real-time monitoring and alarm of reagent Intelligent monitoring, supplements and alarm of cleaning fluid Intelligent monitoring, emissions and alarm of effluent waste overload indication, alarm Real-time self diagnosis, self repair, self protect Maintenance function Optional ratio for sample dilution Unique incubation and washing mode mixing function
Software System	Graphic user interface, touch screen Supporting LIS bidirectional data transmission round-the-clock online remote technical support and maintenance
Weight	65kg
Dimensions(H*W*D)	920*495*515mm

Contact Us

Address: 6th, 2-1-2 Jupiter Technology Building, High-tech Park in Northern, Chongqing, China

Tel: 86-23-6305 3515 / 6308 3850 Fax: 86-23-6305 3515

Web: www.key-smile.com E-mail: keysmile@key-smile.com



**Automatic
Chemiluminescence Immunoassay Analyzer
SMART 3000S**



Professional